

Package: r4sub (via r-universe)

May 16, 2026

Title Easily Install and Load the R4SUB Ecosystem

Version 0.1.0

Description The 'r4sub' package is a meta-package that installs and loads core packages of the R4SUB (R for Regulatory Submission) clinical submission readiness ecosystem. Loading 'r4sub' attaches 'r4subcore', 'r4subtrace', 'r4subscore', 'r4subrisk', 'r4subdata', and 'r4subprofile'.

License MIT + file LICENSE

URL <https://r4sub.github.io/r4sub/>, <https://github.com/R4SUB/r4sub>

BugReports <https://github.com/R4SUB/r4sub/issues>

Depends R (>= 4.2)

Imports cli, r4subcore, r4subdata, r4subprofile, r4subrisk, r4subscore, r4subtrace, rlang, tibble, utils

Suggests knitr, r4subdata, r4subrisk, r4subtrace, r4subprofile, r4subusability, r4subui, rmarkdown, testthat (>= 3.0.0)

VignetteBuilder knitr

Config/testthat/edition 3

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

Config/pak/sysreqs libicu-dev libxml2-dev

Repository <https://r4sub.r-universe.dev>

Date/Publication 2026-03-17 06:06:54 UTC

RemoteUrl <https://github.com/r4sub/r4sub>

RemoteRef HEAD

RemoteSha 8022501b5957c95ad59b50be193be9fd23ce7e6d

Contents

core_packages	2
r4sub_cite	2
r4sub_conflicts	3
r4sub_news	3
r4sub_packages	4
r4sub_status	5

Index	6
--------------	----------

core_packages	<i>Core R4SUB packages</i>
---------------	----------------------------

Description

Returns the names of the R4SUB packages that are automatically attached when `library(r4sub)` is called.

Usage

```
core_packages()
```

Value

A character vector of package names.

Examples

```
core_packages()
```

r4sub_cite	<i>Cite the R4SUB Ecosystem</i>
------------	---------------------------------

Description

Prints citation information for the R4SUB ecosystem and each installed core package. Use this when citing R4SUB tools in a regulatory submission document, scientific paper, or validation report.

Usage

```
r4sub_cite(package = NULL)
```

Arguments

package	Character. Name of a specific R4SUB package to cite. If NULL (default), cites all installed core packages plus the meta-package.
---------	--

Value

Invisibly returns a named list of citation objects, one per package. Called for its side effect of printing citation information to the console.

Examples

```
r4sub_cite()  
r4sub_cite("r4subcore")
```

r4sub_conflicts	<i>Show R4SUB Function Conflicts</i>
-----------------	--------------------------------------

Description

Reports any exported function name collisions between attached R4SUB packages and other loaded packages.

Usage

```
r4sub_conflicts()
```

Value

A tibble with columns: func, r4sub_package, other_package. Returned invisibly. Prints conflicts if any exist.

Examples

```
r4sub_conflicts()
```

r4sub_news	<i>Show R4SUB Ecosystem News</i>
------------	----------------------------------

Description

Prints the NEWS entries for each installed R4SUB ecosystem package. Useful for tracking what has changed across the ecosystem after updating.

Usage

```
r4sub_news(package = NULL)
```

Arguments

`package` Character. Name of a specific R4SUB package to show news for. Must be one of the core R4SUB packages. If NULL (default), shows news for all installed core packages.

Value

Invisibly returns a named list of news database objects, one per package. Called for its side effect of printing NEWS entries to the console.

Examples

```
r4sub_news()
r4sub_news("r4subcore")
```

<code>r4sub_packages</code>	<i>List R4SUB Ecosystem Packages</i>
-----------------------------	--------------------------------------

Description

Returns a tibble of all R4SUB packages with their installed version and current attachment status.

Usage

```
r4sub_packages(include_self = TRUE)
```

Arguments

`include_self` Logical. If TRUE (default), includes the r4sub meta-package itself in the listing.

Value

A tibble with columns: package, version, attached.

Examples

```
r4sub_packages()
```

`r4sub_status`*Check R4SUB Package Installation Status*

Description

Reports the installed version of each R4SUB ecosystem package and highlights any packages that are not installed.

Usage

```
r4sub_status()
```

Value

A tibble with columns: `package`, `installed`. Returned invisibly. Called for its side effect of printing installation status to the console.

Examples

```
r4sub_status()
```

Index

core_packages, [2](#)

r4sub_cite, [2](#)

r4sub_conflicts, [3](#)

r4sub_news, [3](#)

r4sub_packages, [4](#)

r4sub_status, [5](#)